

5MP IP IR Dome Network Camera

ND25TSPA-28



FEATURES

- Fixed lens 2.8mm
- IR distance up to 20 meters
- Support auto white balance, auto exposure, auto gain, AES
- Built in IR cut with Day & Night function
- Support pre-recording function
- Support snapshot, remote recording by schedule setting
- IP66 water proof and IK10 vandal proof

SPECIFICATIONS

Image Sensor	Progressive Scan CMOS
Resolution	5MP
Lens	2.8 fixed Lens
Shutter Speed	1/3s ~ 1/10,000s
Minimum Illumination	0.01 Lux@F1.2, 0 Lux with IR
Day & Night	ICR
BLC Support	Yes
DNR	3D DNR

WDR	Digital WDR
Video Processing	H.265 Video encoding, support dual-stream
Transmission Stream Rate	Dual Stream
Frame Rate	30 fps
Network Interface	RJ45 10/100M Adaptive Ethernet Interface
Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF
Intelligent Alarm	Motion detection, Network disconnect, IP address conflict
System Compatibility	ONVIF
Audio output	Support
Microphone	Built -in
SD Card Slot	Support, 128GB
Power Supply	DC12V±10%, PoE
PoE	IEEE802.3af
IR LED	12pcs
IR Range	20M
Working Temperature	-10 ~ +60°C
Protection	IP66 water proof and IK10 vandal proof
Weight	980g